

Specifications

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Petrol	Dual Cab ST-X PU 4x4 Diesel
Engine									
4.0 litre petrol V6 DOHC								•	
2.5 litre intercooled turbo-diesel, DOHC	•	•	•	•	•	•	•		•
Displacement (cc)	2488	2488	2488	2488	2488	2488	2488	3954	2488
Bore x stroke (mm)	89 x 100	89 x 100	89 x 100	89 x 100	89 x 100	89 x 100	89 x 100	95.5 x 92	89 x 100
Max power (kW@rpm)	106@4000	126@4000	126@4000	126@4000	106@4000	126@4000	126@4000	198@5600	140@4000
Max torque (Nm@rpm)	356@2000	403@2000	403@2000	403@2000	356@2000	403@2000	403@2000	385@4000	450@2000

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Petrol	Dual Cab ST-X PU 4x4 Diesel
Transmission									
6-speed manual	•	•	•	•	•	•	•	•	•
5-speed automatic		Opt	Opt	Opt		Opt	Opt		
5-speed automatic with manual mode								Opt	Opt
Transfer case - Dual range 4x4 with electric 4WD selection	•	•	•	•		•	•	•	•
Ratio 1st manual	4.692	4.692	4.692	4.692	4.692	4.692	4.692	4.368	4.692
Ratio 2nd manual	2.705	2.705	2.705	2.705	2.705	2.705	2.705	2.518	2.705
Ratio 3rd manual	1.747	1.747	1.747	1.747	1.747	1.747	1.747	1.743	1.747
Ratio 4th manual	1.291	1.291	1.291	1.291	1.291	1.291	1.291	1.283	1.291
Ratio 5th manual	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Ratio 6th manual	0.827	0.827	0.827	0.827	0.827	0.827	0.827	0.769	0.827
Ratio Reverse manual	4.260	4.260	4.260	4.260	4.260	4.260	4.260	3.966	4.260
Final drive manual	3.538	3.692	3.692	3.692	3.538	3.692	3.692	3.692	3.692
Ratio 1st automatic		3.827	3.827	3.827		3.827	3.827	3.842	3.827
Ratio 2nd automatic		2.368	2.368	2.368		2.368	2.368	2.353	2.368
Ratio 3rd automatic		1.520	1.520	1.520		1.520	1.520	1.529	1.520
Ratio 4th automatic		1.000	1.000	1.000		1.000	1.000	1.000	1.000
Ratio 5th automatic		0.834	0.834	0.834		0.834	0.834	0.839	0.834
Ratio Reverse automatic		2.613	2.613	2.613		2.613	2.613	2.765	2.613
Final drive automatic		3.538	3.538	3.538		3.538	3.538	3.357	3.538
Transfer ratio - low	2.625	2.625	2.625	2.625		2.625	2.625	2.625	2.625
Transfer ratio - high	1.000	1.000	1.000	1.000		1.000	1.000	1.000	1.000

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Petrol	Dual Cab ST-X PU 4x4 Diesel
Dimensions									
Overall length (mm)	5140	5125	5125	5230	5125	5125	5230	5296	5296
Overall width excluding mirrors (mm)	1795	1850	1850	1850	1850	1850	1850	1848	1848
Overall height (without roof rail)(mm)	1740	1770	1770	1770	1780	1780	1780	1795	1795
Wheelbase (mm)	3200	3200	3200	3200	3200	3200	3200	3200	3200
Track front/rear (mm)	1550/1550	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570
Minimum turning circle kerb to kerb (m)	12.5	13.2	13.2	13.2	13.2	13.2	13.2	13.3	13.3
Tare mass (kg)* manual/automatic	1630*	1750/1776*	1770/1796*	1920/1946	1887	1981/2001	1974/1989	1977/1972	2012/2029
Gross Vehicle Mass (GVM)** (kg)	2860	2860	2860	2860	2860	2860	2860	2805	2805
Carrying capacity (kg) manual/automatic	1230 ^A	1110/1084 ^A	1090/1064 ^A	940/914	973	879/859	886/871	828/833	793/776
Ground clearance (mm) unladen	190	205	205	205	205	205	205	228	228
Overhang - front	800	800	800	800	800	800	800	866	866
Overhang - rear	1140	1125	1125	1230	1125	1125	1230	1230	1230
Angle of approach	32.0	32.0	32.0	32.0	32.0	32.0	32.0	30.0	30.0
Angle of departure	27.5	27.5	27.5	24.0	27.5	27.5	24.0	24.0	24.0
Tray length floor (mm)				1865	1513	1513	1513	1511	1511
Tray length top (mm)				1830	1480	1480	1480	1487	1487
Tray width floor (mm)				1560	1550	1550	1550	1560	1560
Tray width top (mm)				1495	1494	1494	1494	1496	1496
Tray width between wheel arches (mm)				1135	1134	1134	1134	1130	1130
Tray width tailgate opening width (mm)				1435	1435	1435	1435	1432	1432
Tray height (mm)				454	454	454	454	457	457

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Petrol	Dual Cab ST-X PU 4x4 Diesel
Rated Towing Capacity¹									
Trailer with brakes (kg)	3000	3000	3000	3000	2000	3000	3000	3000	3000
Trailer without brakes (kg)	750	750	750	750	750	750	750	750	750
Towball download (kg)	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table
Gross front axle (kg)	1365	1365	1365	1365	1365	1365	1365	1365	1365
Gross rear axle (kg)	1720	1720	1720	1720	1720	1720	1720	1720	1720

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Petrol	Dual Cab ST-X PU 4x4 Diesel
Fuel									
Fuel type - ULP								•	
Fuel type - diesel	•	•	•	•	•	•	•		•
Fuel tank capacity (litres)	80	80	80	80	80	80	80	80	80
Fuel consumption l/100km (combined ADR 81/02) ⁵⁰ (manual)	9.3	9.8	9.8	9.8	9.1	9.8	9.8	13.6	8.5
Fuel consumption l/100km (combined ADR 81/02) ⁵⁰ (automatic)		10.5	10.5	10.5		10.5	10.5	14.0	9.0

Specifications

	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Petrol	Dual Cab ST-X PU 4x4 Diesel
Slate Grey*	•	•	•	•	•	•	•		
Polar White	•	•	•	•	•	•	•		
Burning Red	•	•	•	•	•	•	•		
Deep Sapphire*		•	•	•	•	•	•		

Warranty

3 year / 100,000kms	•	•	•	•	•	•	•	•	•
3 year 24-Hour Roadside Assistance Program	•	•	•	•	•	•	•	•	•
Genuine Nissan Extended Warranty	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt

Single and King Cab models

Towball download	Vehicle Mass
80kg	GVM** (All variants)
100kg	Reduced loaded vehicle mass below GVM** by 30kg
150kg	Reduced loaded vehicle mass below GVM** by 110kg
200kg	Reduced loaded vehicle mass below GVM** by 185kg
250kg	Reduced loaded vehicle mass below GVM** by 250kg
300kg	Reduced loaded vehicle mass below GVM** by 310kg

2WD Dual Cab models

Towball download	Vehicle Mass
70kg	GVM** (All variants)
100kg	Reduced loaded vehicle mass to below GVM** by 40kg
150kg	Reduced loaded vehicle mass to below GVM** by 110kg
200kg	Reduced loaded vehicle mass to below GVM** by 180kg

4WD Dual Cab models

Towball download	Vehicle Mass
150kg	GVM** (All variants)
200kg	Reduced loaded vehicle mass below GVM** by 60kg
250kg	Reduced loaded vehicle mass below GVM** by 130kg
300kg	Reduced loaded vehicle mass below GVM** by 200kg

GVM = Gross Vehicle Mass

If the loaded vehicle mass is reduced as shown in the table, the towball download can be increased correspondingly. Accordingly, if the laden mass is 180kg less than the GVM** a towball download of 200kg is approved (2WD). Different trailer types and different trailer manufacturers have varying towball downloads. The customer will need to contact the trailer manufacturer for information as to the download. Nissan is not able to make any recommendation on the use or suitability of load-levelling or weight distribution devices to be fitted to the vehicle. Customers should contact the manufacturers of these devices for further information.

** GVM includes the driver, passengers, full fuel tank and luggage.

Tare mass = unladen mass of vehicle and 10 litres of fuel, excludes tray body for Cab Chassis vehicles.

Δ Including optional tray.

* Indicates a metallic colour, which is available at extra cost.

∞ Figures have been calculated in accordance with ADR81/02 (combined fuel consumption data).

Actual fuel consumption will vary depending on driving conditions, driver behavior, the condition of your vehicle and the accessories fitted.

† Towing capacity is subject to towbar/towball capacity. The capacity may be reduced if a non genuine Nissan towbar is fitted. The permitted download is directly related to the laden mass of vehicle. The maximum towball download is 300kg.

- The fitment of front protection systems and accessories having a combined weight in excess of 55 kgs will require a Positive Bonnet Restraint System & Nissan H/D front suspension springs.



Genuine Nissan Extended Warranty

To find how easily you can extend your new vehicle warranty, ask your Nissan Dealer or phone 1800 035 035 during normal business hours. Good for you, great for your Nissan.

To finance your new Nissan



FINANCIAL SERVICES

1800 035 035
www.nissanfs.com.au

Finance and Insurance solutions designed for your Nissan. Designed for you.



Interior cloth seat trim (ST-X Dual Cab).



Interior cloth seat trim (RX Single Cab, RX/ST Dual Cab and RX/ST-X King Cab).

All illustrations, information and specifications presented and referred to in this brochure were correct at the time when this brochure was approved for printing. The colours in the photographs may vary from actual colours. However, Nissan Motor Co (Australia) Pty. Ltd. reserves the right, subject to the laws of Australia and/or the regulations of any competent authority which may apply from time to time, at its discretion at anytime and without prior notice to discontinue or change the models, features, specifications, designs and prices of the products referred to in this brochure and any optional equipment therefore without incurring any liability whatsoever to any purchaser or prospective purchaser of any such products. Some of the items referred to herein are optional at extra cost. Some options may be required in combination with other options. Always consult your Nissan Dealer for the latest information on models, specifications, features, prices, options and availability. Nissan Motor Co (Australia) Pty. Ltd. ACN 004 663 156. Updated May 2010. 2010MY. NAV0353